



TPU Single-mode Armored Fiber Cable, 8-core

Product Number: 990207

Product Overview

The G202-xxUSM-8LC is a eight-core single-mode finished fiber cable, which is mainly used with audio and video optical fiber extenders. This eight-core single-mode 9/125 G657.A1 fiber with LC-type connectors can transmit up to 2000 meters while maintaining a 10Gbps bandwidth. Different from generic fiber cables, Beetek designed their fiber using tough and wear-resistant TPU sheathing, and the inside uses stainless steel armored tube, Kevlar and a metal braided structure. This structure ensures the cable has strong tensile and compressive strength. At the end points, the product is also equipped with integrated LC connectors, which are not easily broken like their generic counterparts. Plus, the cable comes with a captive dust cap and Beetek's patented aluminum connector protector as standard to ensure repeated use in harsh environments.




*Fiber length, core quantity and connector types can all be customized.



Product Features

- Adopts high-quality YOFC single-mode G657.A1 fiber core.
- The transmission rate is 10Gbps up to 2000 meters.
- The pliable yet rugged TPU outer sheath and built-in armored piping structure make the cable both durable and flexible at the same time.
- The interior uses DuPont Kevlar and metal woven reinforcement structure.
- LC connectors are integrated into the cable for strong and reliable connections.
- Maintains the characteristics of anti-freezing, wear resistance, tensile resistance and pressure resistance. Built to last in all conditions.
- Comes with captive LC dust caps and Beetek' s patented connector protector.
- Comes standard with Velcro straps for easy storage and deployment.
- Optional DF and PCD Series cable reels are available for superior cable management.

Product Detail Drawing




Product Specifications

Name	Specifications
Product Type	G202-xxUSM-8LC
Connector Type	LC
Connector Color	Dark blue
Fiber Type	Single-mode (9/125 μm)
Fiber Wavelength	1310nm~1550nm
Fiber Core Brand	YOFC
Number of cores	8
Branch Length	1 meter
Reinforcement Structure	Dupont Kevlar with metal weave
Structural Layers	Fiber core + Cladding + Coating + Spiral-armored tube + Kevlar + Aluminium braid + TPU outer jacket
Jacket Outer Diameter	5.0mm \pm 0.1mm
Jacket Material	Matt Frosted TPU
Jacket Color	Matte Black
Spiral Tube Diameter	2.8mm \pm 0.1mm

Name	Specifications
Spiral Tube Material	SUS 201
Spiral Tube Color	Silver
Core Cladding Diameter	0.6mm±0.05mm*8
Core Cladding Material	PVC
Core Cladding Color	Blue, Orange, Green, Brown, White, Gray, Black, Red
Core Diameter	9.0μm±0.4μm
Cladding Diameter	124.8μm±0.7μm
Cladding out of roundness	≤0.7%
Core/cladding Concentricity Error	≤0.5μm
Coating Diameter	245±5μm
Coating layer out of roundness	≤6.0%
Cladding/coating Concentricity Error	≤12.0μm
Attenuation Coefficient	1310nm≤0.4dB/km, 1550nm≤0.3dB/km
Tensile (LC connector)	Long-term 50N, short-term 60N
Tensile (optical cable)	Long-term 400N, short-term 800N
Compressive Strength	Long-term 2000N/10cm, short-term 3000N/10cm
Linear Rolling	3000N/10cm armor layer deformation < 0.3mm, additional attenuation < 0.2dB
Minimum Bending Radius	Dynamic > 10D, Static > 20D (*D is the outer diameter of the cable)
Transmission Rate	10Gbps within 2000 meters
Operating Temperature	-20°C~70°C
Available Lengths	50M, 100M, 150M, 200M, 300M
Included Accessories	Connector protector BH03*2, Dust cap LCF01*16

Product Size



Connector Type : LC
Connector Size : 4.52mm*4.52mm*21.5mm
Fiber Core Brand : YOFC
Branch Length : 1M



Full catalog



WhatsApp



Instagram



Facebook